

## TITAN II 7200 RECTIFIER



Titan II rectifiers have market's leading power density bringing along diminutive space requirements. The highest energy efficiency enables lower energy consumption and leads to smaller environmental footprint.

We are focusing on continuous improvement of total cost of ownership. Titan II rectifiers combined with advanced controlling and monitoring units enable not only squeezing CAPEX but also OPEX.

Titan II 7200 rectifiers are three phase design with power factor correction and forced convection cooling. The constant output power characteristic supplies the specified power over the full output voltage range. The rectifier employs the state-of-the-art technology and provides excellent performance in the extended temperature range, wide input voltage range, and low THD. The advanced technology is the key factor of the success of this rectifier and it offers a cost effective and reliable solution.

Easy installation is secured as all C&D rectifiers are hot-pluggable and have connectors at rear.

### Main Features

- Three-phase, 208/240 or 480 Vrms input
- Efficiency: 90 %
- Low THD: <5%
- Hot swappable, no system shutdown for maintenance
- Wide input voltage range: 176-264 or 264-530 Vrms
- Power factor correction (0.99)
- Constant output power characteristic
- User friendly LCD Display

### Applications

Typically Titan II 48 V Power Systems are used in:

- Telecom central offices
- Data centers
- Ferro-replacement

## Technical Specifications

### Input

Mains voltage	176 – 264 Vrms (208/240 Vac nominal), or 264 – 530 Vrms (480 Vac nominal)
Mains frequency	45-65 Hz
Harmonic distortion (THD)	< 5%
EMI/RFI	FCC class B CISPR 22 class B
Protection	Circuit Breaker

### Output

Nominal system voltage	54 V
Operating voltage range	50-60 V
Power limitation	7200 W
Current limitation	150 A
Overvoltage protection	60.5 V
Load sharing	yes
Protection	Internal fuse

### Ordering Information

Rectifier, 208 Vac input	162.1003.00
Rectifier, 480 Vac input	162.1002.00

### General

Efficiency	90 %
Control and monitoring	Intelligent CSU
User interface	LCD & LED
Dimensions (W x H x D)	481 x 132 x 484 mm 18.9 x 5.2 x 19.1 in
Weight	22 kg 48.5 lb
Standards	
• Safety	EN / IEC 60950 UL 60950
• EMI (radiated)	FCC class B CISPR 22 class B
• Environment	RoHS 5 compliant
Cooling	Fan cooled
Acoustics	55 dB (A)
Operating temperature	-5 - +55 °C +23 - +131 °F

## TECHNOLOGIES, INC.

1400 Union Meeting Road  
P.O. Box 3053 • Blue Bell, PA 19422-0858  
(215) 619-2700 • Fax (215) 619-7899 • (800) 543-8630  
customersvc@cdtechno.com  
www.cdtechno.com

Any data, descriptions or specifications presented herein are subject to revision by C&D Technologies, Inc. without notice. While such information is believed to be accurate as indicated herein, C&D Technologies, Inc. makes no warranty and hereby disclaims all warranties, express or implied, with regard to the accuracy or completeness of such information. Further, because the product(s) featured herein may be used under conditions beyond its control, C&D Technologies, Inc. hereby disclaims all warranties, either express or implied, concerning the fitness or suitability of such product(s) for any particular use or in any specific application or arising from any course of dealing or usage of trade. The user is solely responsible for determining the suitability of the product(s) featured herein for user's intended purpose and in user's specific application.

Copyright 2009 C&D TECHNOLOGIES, INC. Printed in U.S.A. 10-1022 1009/CD